

A MONOCHROMATIC VACUUM ULTRAVIOLET LIGHT SOURCE
FOR PHOTOLITHOGRAPHY APPLICATIONS BASED ON
A HIGH-PRESSURE MICROHOLLOW CATHODE DISCHARGE

INTRODUCTION

This application claims the benefit of priority of U.S. Provisional Application Serial No. 60/210,212 filed June 8, 2000.

5 This work was supported by the United States National Science Foundation (NSF) under awards PHY-9722438 and PHY-9722438, ECS-98033997, and CTS-0078618; and by the U.S. Defense Advanced Research Projects Agency (DARPA) under contract DAAD19-99-1-0277. The U.S. Government has certain
10 rights in this invention.

FIELD OF THE INVENTION

This invention relates to gas discharge devices which utilize a cathode and dielectric spacer having a single hole
15 or an array of holes therein and an arbitrarily shaped anode, and methods of use thereof.

BACKGROUND OF THE INVENTION

Optical lithography is used e.g. by the semiconductor
20 industry to generate the small features which determine the size of the electronic circuits on semiconductor wafers. Mercury arc lamps have been used as light sources for such photolithography.

In order to reduce chip feature sizes excimer laser
25 have been used such as the 248 nm KrF laser. Excimer lasers used for deep-UV photolithography are discharge pumped. Efficiencies are on the order of one percent to two percent.

They only exist as pulsed devices with pulse duration of tens of μ s determined by the plasma stability. Voltages required to operate them are in the multi-kV range.

Non-coherent excimer radiation and other sources of
5 monochromatic vacuum ultraviolet (VUV) light are also being explored. Excimers are temporary chemical compounds composed of atoms which under normal conditions would not form a stable molecule. A stable excimer molecule is only formed in a high-energy, or excited, state. The excimer molecule as a whole
10 decays into the constituent atoms upon emission of characteristic radiation. Excimers have been produced e.g. by applying beams of energized particles to inert gases. The gas is present under substantial pressure. Another means of producing excimers are high-pressure discharge plasmas such
15 as e.g. plasmas produced in microhollow (MHC) cathode discharges.

The present invention provides a method and apparatus for the production of intense hydrogen Lyman- α as well as Lyman- β emissions and other atomic emissions from a
20 microhollow cathode (MHC) discharge operated in a mixture of high-pressure Neon (Ne), Helium (He), or Argon (Ar) with a small admixture of Hydrogen (H_2), Nitrogen (N_2), or Oxygen (O_2).

SUMMARY OF THE INVENTION

25 An object of the present invention is to provide a light source comprising a sealed, light-transmissive tube containing high pressure gases or high pressure gas mixtures at a high pressure (100 Torr to 10,000 Torr) with a discharge device consisting of a first conducting electrode (cathode)
30 having a single hole or a plurality of holes therein and a second conducting electrode (anode, which may or may not have a hole or holes similar to the one(s) in said first electrode), mounted within said tube and separated from first electrode by an insulating spacer with a hole or holes therein
35 similar to hole(s) in said first electrode; and electrical

means for coupling electrical energy to said first and second electrodes for producing discharges in each of the holes in said first electrode. The exact shape of the hole(s) in said first electrode and the insulating spacer are not important
5 as long as the area of the hole(s) is in the range from 0.001 mm² and 1 mm² (microhollow cathode (MHC) discharge).

Another object of the present invention is to provide a method of generating intense hydrogen Lyman- α or Lyman- β or atomic oxygen and nitrogen emissions in the spectral range
10 from 100 nm to 150 nm by placing the MHC discharge device into a container which contains a high pressure gas or high pressure gas mixture.

Another object of the present invention is to provide a method of generating an extended source of higher irradiance
15 over an extended area by using an array of MHC discharge sources operated in parallel.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows an MHC discharge device.

20 Figure 2 shows emission spectrum from a MHC discharge operated in high-pressure with pure Ne gas.

Figure 3a and 3b show emission spectra from a MHC discharge operated in high pressure with a Ne/H₂ gas mixture.

Figure 4 shows the emission spectrum from a MHC discharge
25 operated in high pressure with an Ar/O₂ gas mixture.

DETAILED DESCRIPTION

MHC discharges are conceptually simple, efficient sources of excimer radiation. Excimer emissions are based on
30 the formation of excited molecular dimer complexes, known as excimers, in, for example, the rare gases. Excimer molecules are formed via three-body collisions involving a metastable rare gas atom and two ground state atoms and via other collisional interactions between electrons and atomic and
35 molecular ions. The conditions for efficient excimer

formation require a sufficiently large number of electrons with energies above the threshold for the formation of metastable rare gas atoms. Rare gas excimer emission spectra are dominated by the second excimer emission continua of the pure rare gas molecules which are emitted in a transition from the lowest-lying excited bound excimer state to the repulsive ground state. The peaks in the second continua of the rare gases are at wavelengths of 170 nm (Xe), 145 nm (Kr), 128 nm (Ar) and 84 nm (Ne), respectively. The first excimer continua of the pure rare gases can be observed as a shoulder on the short wavelength side of the second continua.

In one embodiment, the present invention provides a light source comprised of a sealed, light-transmissive tube containing a gas or a gas mixture at high pressures ranging from 100 Torr to 1500 Torr; a first electrode (cathode) having a single hole or a plurality of holes therein mounted within the light-transmissive tube and a second electrode (anode, which may or may not have a hole or holes similar to the hole(s) in said first electrode) mounted within said tube and separated from the cathode by an insulating spacer with a hole or holes similar to the hole(s) in said first electrode. The exact shape of the holes in said first electrode and the insulating spacer are not important as long as the area of the holes is in the range from 0.001 mm² and 1 mm². Means are provided for coupling electrical energy to said first and second electrodes for producing MHC discharges in each of the holes in said first electrode. Both electrodes, i.e. the anode and the cathode have a thickness of from about 0.05 mm to about 0.5 mm. The insulating spacer has a thickness of from about 0.1 mm to 1 mm. The gas or gas mixture is present in the device at high pressure in the range of about 100 Torr to about 10,000 Torr. The gas may be stagnant or flowing through the electrodes of the MHC discharge device.

In a preferred embodiment the high pressure gas is Ne, He, or Ar. The high pressure gas may be a single gas or a

mixture of two or more gases, i.e. a primary gas and secondary gas(es). In a preferred embodiment the secondary gases which form a mixture with the primary gases may be selected from H_2 , N_2 , or O_2 . In an especially preferred embodiment the high pressure gas is a mixture of Ne and H_2 , Ne and N_2 , Ar and O_2 , He and N_2 , or He and O_2 .

The term "primary gas" is meant to refer to the gas which constitutes the majority of the high pressure gas mixture, when the high pressure gas is composed of a mixture of gases, or of a sole gas. The term "secondary gas" is meant to refer to a gas or gases present as a minority percentage of the total gas mixture when the high pressure gas is present as a mixture of gases. Two or more secondary gases may combine with a primary gas to form the high pressure gas mixture. Preferably, the amount of secondary gas, i.e., N_2 , H_2 and O_2 is less than 1% of the total gas pressure in the light source.

Figure 1 depicts a MHC discharge device. The discharge device includes a cathode 2 and an anode 4 mounted within a discharge chamber 6. The discharge chamber 6 is typically sealed and contains a high pressure gas or high pressure gas mixture at a prescribed pressure, P. A power source supplies energy to the discharge device. Supply voltages (V_0) typically 300-1000 V are provided by a direct current power supply. Other modes of electrical power supply can be used such as an alternating current power supply with frequencies ranging from 100 Hz to 500 kHz or a radio frequency power supply with frequencies in the range from 1 MHz to 50 MHz, or pulse generators providing electrical pulses of 10^{-8} s to 0.1 s in duration.

A MHC discharge consists of a cathode with a single hole or a plurality of holes with hole diameters, D, of about 30 - 1,000 μm separated from the anode by a thin sheet of dielectric spacer 12. The hole or holes are formed in the surface of the cathode and in the insulating spacer and they

may or may not be formed in the anode. The exact shape of the hole(s) in said first electrode and the insulating spacer are not important as long as the area of the hole(s) is in the range from 0.001 mm² and 1 mm² (microhollow cathode (MHC) discharge). Discharges in such geometry show several modes of operation as a function of gas pressure (P), hole diameter (D) 10, cathode-anode separation (d) 14 and discharge current (I). V_{dis}, R_c, V, R_{CVR} and Ground are components of the electric circuit. V 20 is the externally applied voltage, V_{dis} 22 refers to the discharge sustaining voltage, and R_c 16 and R_{CVR} 18 are appropriately chosen resistors that allow the proper operation of the MHC discharge and allow us to monitor the discharge properties. The exact shape of the hole(s) in said first electrode and the insulating spacer are not important as long as the area of the hole(s) is in the range from 0.001 mm² and 1 mm².

The conditions in an MHC discharge satisfy the two criteria necessary for excimer formation, i.e., the MHC discharges have a sufficiently large number of electrons with energies larger than the ionization/excitation energy of the noble gas atoms; and the MHC discharges can be operated at pressures that are high enough so that the three-body collisions required for excimer formation occur with sufficient frequency. The electrode geometry for a single hole MHC excimer lamp, as depicted in Figure 1, consists of two metal plates with an opening, separated by dielectric spacer. Alternatively, the anode may consist of an electrode without holes.

In one embodiment, both cathode and anode consist of molybdenum. The electrodes are separated by a dielectric spacer. In a preferred embodiment, the dielectric spacer is alumina (AL₂O₃) or mica which withstand high temperatures. The hole may have diameters from 30 μm to 1000 μm. The electrodes may be of any material which is conductive. The dielectric

spacer between the electrodes may be of any insulator material. The electrodes may be on the order of about 30 - 250 μm thick and the dielectric spacer between them may be on the order of about 100 - 500 μm thick. The exact shape of the hole(s) in said first electrode and the insulating spacer are not important as long as the area of the hole(s) is in the range of from about 0.001 mm^2 to about 1 mm^2 .

Typical discharge sustaining voltages are 150-300 V, with currents ranging from 0.1 mA to 20 mA (dc equivalent).

10 The electrodes are placed in a sealed vessel filled with high pressure gas or high pressure gas mixture at a high pressure. The gas filled vessel, which allows optical access, preferably, from the front and back of the vessel. Electrical connections supply power to the electrodes, and gas inlets and
15 outlets which allow evacuation of the vessel and filling with the desired gas mixture. This design also permits flow of the gas through the hole in the discharge device. Preferably, the window is MgF_2 or LiF which are transparent for deep UV light.

Figure 2 depicts the emission spectrum from an MHC discharge in pure Ne at 740 Torr in the wavelength region 70-100 nm recorded with a full width at half maximum (FWHM) spectral resolution of 0.25 nm. The spectrum has two characteristic features, i.e., a sharp asymmetric peak in the 73-78 nm region with maximum intensity near 74.5 nm; and a broad continuum from 80 to 88 nm. The first peak in the 73-78 nm region contains the two Ne resonance lines at 73.5 and 74.3 nm respectively, as well as emissions from the Ne_2^* first excimer continuum, whereas the broad continuum in the 80-88 nm region is due to the Ne_2^* second excimer continuum.

30

Another embodiment of the present invention provides a method of generating intense hydrogen Lyman- α or Lyman- β emissions or atomic oxygen and nitrogen emissions in the spectral range from 100 nm to 150 nm by placing the MHC discharge device into a sealed container which contains a high

Sub
AD
Cmt

SWdy
A2
End

pressure gas or high pressure gas mixture. The high pressure gas mixture may be stagnant or may be flowed through the hole(s) in the MHC discharge device. Figure 3 shows emission spectra from a MHC discharge operated in high-pressure Ne with a small admixture of H_2 at 0.5 Torr. Two figures are shown, a scan covering the entire wavelength range from 70 to 125 nm (a) and a scan covering the wavelength range of the Ne resonance lines and the Ne_2^* second excimer continuum using an expanded intensity scale (b). The most striking observations from Figure 3(a) are the very weak intensity observed in the range of the Ne and Ne_2^* emission and the dominance of the hydrogen Lyman- α line at 121.6 nm. There is also a distinct Lyman- β emission line at 102.5 nm. The expanded intensity scale in Figure 3(b) shows that all Ne/ Ne_2^* emission features have been reduced considerably, particularly the second continuum. The emission of the hydrogen Lyman- α emission is due to a near-resonant energy transfer between the Ne_2^* and the H_2 molecules causing the break-up of the H_2 molecule into two H atoms and the simultaneous excitation of one H atom to the $n=2$ excited state followed by the emission of the H Lyman- α line at 121.6 nm when the excited H($n=2$) atom decays to the $n=1$ ground state.

The presence of a relatively intense hydrogen Lyman- β line in the spectrum shown in Figure 3(a) cannot be explained by the same process since the maximum energy contained in the Ne_2^* excimer responsible for the emission of the second continuum (15.5 eV) is below the minimum energy required for H($n=3$) formation (16 eV). A near resonant energy transfer process involving excited, and likely metastable, Ne atoms and/or vibrationally excited Ne_2^* excimers are responsible for the emission of the H Lyman- β emission.

Figure 4 shows the emission spectrum from a MHC discharge operated in high pressure with an Ar/O_2 gas mixture. There is a sharp peak in the 120-140 nm range, and particularly at 130.2-130.5 nm.

In another aspect, MHC discharges provide extended sources, rather than a point source, with irradiance covering an extended area. This is achieved by parallel operation of the MHC discharges.

5 In another aspect, the present invention provides large array extension using a distributed, resistive ballast. This is achieved by using a semi-insulating material as anode material. In producing distributed operation, the light source is made up of a sealed, light-transmissive tube containing
10 gases or gas mixtures at a high pressure, an array of microhollow cathode discharges configured with a plurality of cathodes and a distributed anode, electrical means for coupling electrical energy to the electrodes, and an insulating spacer. The array of microhollow cathode
15 discharges is made of multiple microhollow cathode discharges, wherein each microhollow cathode discharge has a first electrode (or cathode) mounted within said light-transmissive tube. The first electrode has a conductor with a single hole or a plurality of holes therein. Each of said holes in the
20 conductor has an arbitrary shape and an area ranging from 0.001 mm^2 to 1 mm^2 . The anode is made of a distributed resistive ballast comprising a semi-insulating material mounted within the light-transmissive tube and spaced apart from the adjoining first electrode of the microhollow cathode
25 discharge array by an insulator which has a hole or holes similar to the hole(s) in the first electrode. Electrical means are used for coupling electrical energy to said first electrodes and anode for producing discharges in each of the holes in said first electrode. Both the first electrodes of
30 the microhollow cathode discharge arrays and the anode have thicknesses which may range from 0.05 mm to 0.5 mm. The insulating spacer may have a thickness ranging from 0.1 mm to 1 mm. A preferred semi-insulating material is silicon. This distributed array light source allows generation of arrays of
35 MHC discharge excimer sources of any size, limited only by the

thermal loading of the ballast resistor. In order to cool the high pressure gas, and to keep it clean, the array may be operated with gas flow by fabricating holes in the semi-insulating layer and anode conductor.

Year	1974-1975	1975-1976	1976-1977	1977-1978	1978-1979	1979-1980	1980-1981	1981-1982	1982-1983	1983-1984	1984-1985	1985-1986	1986-1987	1987-1988	1988-1989	1989-1990	1990-1991	1991-1992	1992-1993	1993-1994	1994-1995	1995-1996	1996-1997	1997-1998	1998-1999	1999-2000	2000-2001	2001-2002	2002-2003	2003-2004	2004-2005	2005-2006	2006-2007	2007-2008	2008-2009	2009-2010	2010-2011	2011-2012	2012-2013	2013-2014	2014-2015	2015-2016	2016-2017	2017-2018	2018-2019	2019-2020	2020-2021	2021-2022	2022-2023	2023-2024	2024-2025	2025-2026	2026-2027	2027-2028	2028-2029	2029-2030	2030-2031	2031-2032	2032-2033	2033-2034	2034-2035	2035-2036	2036-2037	2037-2038	2038-2039	2039-2040	2040-2041	2041-2042	2042-2043	2043-2044	2044-2045	2045-2046	2046-2047	2047-2048	2048-2049	2049-2050	2050-2051	2051-2052	2052-2053	2053-2054	2054-2055	2055-2056	2056-2057	2057-2058	2058-2059	2059-2060	2060-2061	2061-2062	2062-2063	2063-2064	2064-2065	2065-2066	2066-2067	2067-2068	2068-2069	2069-2070	2070-2071	2071-2072	2072-2073	2073-2074	2074-2075	2075-2076	2076-2077	2077-2078	2078-2079	2079-2080	2080-2081	2081-2082	2082-2083	2083-2084	2084-2085	2085-2086	2086-2087	2087-2088	2088-2089	2089-2090	2090-2091	2091-2092	2092-2093	2093-2094	2094-2095	2095-2096	2096-2097	2097-2098	2098-2099	2099-2100	2100-2101	2101-2102	2102-2103	2103-2104	2104-2105	2105-2106	2106-2107	2107-2108	2108-2109	2109-2110	2110-2111	2111-2112	2112-2113	2113-2114	2114-2115	2115-2116	2116-2117	2117-2118	2118-2119	2119-2120	2120-2121	2121-2122	2122-2123	2123-2124	2124-2125	2125-2126	2126-2127	2127-2128	2128-2129	2129-2130	2130-2131	2131-2132	2132-2133	2133-2134	2134-2135	2135-2136	2136-2137	2137-2138	2138-2139	2139-2140	2140-2141	2141-2142	2142-2143	2143-2144	2144-2145	2145-2146	2146-2147	2147-2148	2148-2149	2149-2150	2150-2151	2151-2152	2152-2153	2153-2154	2154-2155	2155-2156	2156-2157	2157-2158	2158-2159	2159-2160	2160-2161	2161-2162	2162-2163	2163-2164	2164-2165	2165-2166	2166-2167	2167-2168	2168-2169	2169-2170	2170-2171	2171-2172	2172-2173	2173-2174	2174-2175	2175-2176	2176-2177	2177-2178	2178-2179	2179-2180	2180-2181	2181-2182	2182-2183	2183-2184	2184-2185	2185-2186	2186-2187	2187-2188	2188-2189	2189-2190	2190-2191	2191-2192	2192-2193	2193-2194	2194-2195	2195-2196	2196-2197	2197-2198	2198-2199	2199-2200	2200-2201	2201-2202	2202-2203	2203-2204	2204-2205	2205-2206	2206-2207	2207-2208	2208-2209	2209-2210	2210-2211	2211-2212	2212-2213	2213-2214	2214-2215	2215-2216	2216-2217	2217-2218	2218-2219	2219-2220	2220-2221	2221-2222	2222-2223	2223-2224	2224-2225	2225-2226	2226-2227	2227-2228	2228-2229	2229-2230	2230-2231	2231-2232	2232-2233	2233-2234	2234-2235	2235-2236	2236-2237	2237-2238	2238-2239	2239-2240	2240-2241	2241-2242	2242-2243	2243-2244	2244-2245	2245-2246</
------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-------------